


POM KEPITAL TS-25H		Grade		
- KEPITAL TS-25H ()		Grade .		
-		, PV 가 .		
		ISO 1183	g/cm ³	1.39
		ISO 1133	g/10min	24
(23 , 50 %RH)		ISO 62	%	0.2
(1.8 MPa)		ISO 75		98
		UL 94	–	HB
(10 /min)		ISO 11357		168
		ISO 11359	X 10 ⁻⁵ /	10
		ISO 527	MPa	59
		ISO 527	%	9.0
		ISO 527	%	23.0
		ISO 178	MPa	83
		ISO 178	MPa	2,550
Charpy (Notched, 23)		ISO 179/1eA	kJ/m ²	5.5
		IEC 60093	Ω	1x10 ¹⁶
		IEC 60093	Ω • cm	1x10 ¹⁴
		IEC 60243-1	kV/mm	-
(, t = 2 mm)		ISO 294-4	%	2.1
		ISO 1043	-	POM

Revision No : 5 (2021-11-08)



1

Mold	Bn(Nozzle)	B3(Metering)	B2(Compression)	B1(Feeding)	Hopper
60 ~ 80	180 ~ 210	190 ~ 200	180 ~ 190	170 ~ 180	60 ~ 80

Tel: 031- 436 -1300